



### **Function**

Guiding elements are designed to prevent metal to metal contact between components of hydraulic systems e.g. piston and cylinder barrel or shaft and cylinder head.

### **Features**

- ⇒ Normally cut at an angle for easy installation, but also available as non-split version
- ⇒ Low dynamic friction.
- ⇒ Low break-away forces after long standstills.

### **Application**

Reciprocating pistons and rods in hydraulic cylinders, plungers.  
Max. speed 4 m/s, radial loads max. 70 N/mm<sup>2</sup>.

### **Installation**

Snap-in installation.

#### **Seal housing recommendation**

<b>Tolerances</b>	<b>[mm]</b>	
L < 10mm	+ 0.2	
L ≥ 10mm	+ 0.3	
∅ NA	H8	
∅ NI	h9	
<b>Surface roughness</b>	<b>Rtmax [μ]</b>	<b>Ra [μ]</b>
Bottom of groove	≤ 6.3	≤ 1.6
Face of groove	≤ 15	≤ 3
<b>Sliding surface</b>	<b>Rtmax [μ]</b>	<b>Ra [μ]</b>
PU, elastomeres	≤ 2.5	≤ 0.1-0.5
PTFE	≤ 2	≤ 0.05-0.3

#### **Profile description**

***Guide Ring***  
***BWR01***