

Wipers

Profile	Type
	WR01
	WR01A
	WR02
	WR02A
	WR02B
	WR02C
	WR03
	WR04
	WR07
	WR08
	WR11
	WR12
	WR13
	WR13_E2
	WR14
	WR15
	WR17
	WR18

Rod seals

Profile	Type
	RS01
	RS01A
	RS01B
	RS02
	RS02A
	RS03
	RS04
	RS05
	RS08
	RS09
	RS09A
	RS09B
	RS91
	RS16
	RS17
	RS17A
	RS17B
	RS17C
	RS17D
	RS17E
	RS19
	RS20
	RS35

Piston seals

Profile	Type
	PS01
	PS01A
	PS01B
	PS02
	PS02A
	PS03
	PS04
	PS05
	PS08
	PS08B
	PS08C
	PS08D
	PS08E
	PS08F
	PS81
	PS09
	PS16
	PS17
	PS19
	PS20
	PS23
	PS35

Symmetrical seals

Profile	Type
	PRS06
	PRS06A
	PRS06B
	PRS06C
	PRS06D
	PRS06E
	PRS07
	PRS10SP
	PRS10-12
	PRS13-15
	PRS18
	PRS19B
	PRS19C
	PRS19D
	PRS22
	PRS99

Static seals & O-rings

Profile	Type
	FL01A
	FL02B
	OR
	ORH

Special profiles

Besides the listed standard profiles we can also deliver special profiles and machined parts in line with customer's drawings, or in special geometries developed by us in line with the requirements.

Back-up rings

Profil	Type
	BUR08
	BUR09
	BUR10
	BUR11
	BUR12
	BUR13

Guide rings

Profile	Type
	BWR01
	BWR02
	BWR03
	BWR04
	BWR05
	BWR06
	BWR07
	BWR08

Rotary seals

Profile	Type
	OS01
	OS02
	OS08
	R03
	R04
	R04A
	R05
	R05A
	VR06
	VR07
	R08
	R09
	R10
	R11
	RS19A
	PS19A

Additional standard profiles

Profiles		Profiles	

Mining seals

Profile	Type
	P50
	P51
	P51G
	P52
	P53
	P54
	R50
	R51
	R52
	R53
	W50
	W51
	W53
	W54
	BWR01-P
	BWR01-R
	P58

Materials

Description		Application temp.	Hardn. at 20°C
PU red U203-R95		-30 to +105°C	Shore A 95 +/-2
PU green U203-G95		-30 to +105°C	Shore A 95 +/-2
PU FDA light blue U203-B95		-30 to +105°C	Shore A 95 +/-2
PU FDA natural U203-95FDA		-30 to +105°C	Shore A 95 +/-2
PU MoS ₂ grey U203-GM95		-30 to +105°C	Shore A 95 +/-2
PU 57 Shore D dark blue U203-D57		-30 to +90°C	Shore D 57 +/-2
PU 57 Shore D + MoS ₂ grey U203-D57G		-30 to +90°C	Shore D 57 +/-2
NBR black N107-B85		-25 to +100°C	Shore A 85 +/-5
NBR 95 black N109-B95		-25 to +100°C	Shore A 95 +/-5
NBR FDA white N111-W85		-22 to +100°C	Shore A 85 +/-3
H-NBR black HN112-B85		-25 to +150°C	Shore A 85 +/-5
FPM brown F109-BR85		-20 to +210°C	Shore A 85 +/-5
FPM FDA brown F110-BR85		-20 to +210°C	Shore A 85 +/-5
FPM black F111-B85		-25 to +210°C	Shore A 85 +/-5
EPDM black E131-B85		-50 to +130°C	Shore A 85 +/-5
EPDM FDA white E132-W85		-50 to +100°C	Shore A 85 +/-3
EPDM KTW black E133-W270		-40 to +120°C	Shore A 85 +/-5
Silicone FDA red S102-R85		-55 to +210°C	Shore A 85 +/-5
Silicone FDA blue S103-BL85		-55 to +180°C	Shore A 85 +/-3
AFLAS black AF101-B85		-15 to +210°C	Shore A 85 +/-5
POM FDA white P101-WE		-60 to +100°C	-
PA FDA natural A112-WC		-30 to +105°C	-
PTFE-F grey T105-G		-200 to +260°C	Shore D 55 - 60
PTFE-P FDA white T101-W		-200 to +260°C	Shore D 51 - 65
PTFE-40% Bronze brown T110-BR40		-200 to +260°C	Shore D 62 - 67
PTFE-40% Bronze blue T115-BR40		-200 to +260°C	Shore D 62 - 67
PTFE-60% Bronze brown T120-BR60		-200 to +260°C	Shore D 65 - 70
PTFE-25% Carbon grey T125-C25		-200 to +260°C	Shore D 62 - 67

We further deliver parts made of different PTFE compounds, PEEK, various Polyamides, Polyimides, PETP and other materials.

The indicated low temperatures are a general guideline only, because the function of the seal at low temperature also depends on the seal design, the service conditions, and on the surrounding metal parts. The indicated high temperatures may be exceeded, but this reduces the service life.

More detailed information you can find in our material catalog, or you consult our application technicians.